

READ BEFORE USING

INSTALLATION INSTRUCTIONS FOR TWO-PIECE BLEED SCREW – PIPE THREAD STYLE ADAPTER

General Information

- Threads in caliper must be clean and dry before installing the new bleed screw adapter.
- Carefully remove any old sealant and brake fluid from the threads in the caliper body.
- Do not contaminate the interior fluid passages in the caliper.
- Use an inch-pound torque wrench only!**

Installation

- Adapter fitting into caliper:**
Torque to 125-150 **in-lb** (wrench size = 10mm)
- Bleed screw fitting:**
Torque to 40 **in-lb** (wrench size = ¼")
 - Bleed screw should be installed into adapter fitting with clean, dry threads.
 - Do not use sealant or thread locking compound on bleed screw.

IMPORTANT: Read disclaimer of warranty included with the product.

READ BEFORE USING

INSTALLATION INSTRUCTIONS FOR TWO-PIECE BLEED SCREW – PIPE THREAD STYLE ADAPTER

General Information

- Threads in caliper must be clean and dry before installing the new bleed screw adapter.
- Carefully remove any old sealant and brake fluid from the threads in the caliper body.
- Do not contaminate the interior fluid passages in the caliper.
- Use an inch-pound torque wrench only!**

Installation

- Adapter fitting into caliper:**
Torque to 125-150 **in-lb** (wrench size = 10mm)
- Bleed screw fitting:**
Torque to 40 **in-lb** (wrench size = ¼")
 - Bleed screw should be installed into adapter fitting with clean, dry threads.
 - Do not use sealant or thread locking compound on bleed screw.

IMPORTANT: Read disclaimer of warranty included with the product.