

READ BEFORE USING

INSTALLATION INSTRUCTIONS FOR TWO-PIECE BLEED SCREW – METRIC THREAD STYLE ADAPTER

General Information

- •Bleed screw and adapter fitting should both be installed with clean, dry threads.
- •Do not use sealant or thread locking compound on bleed screw or adapter fitting.
- Do not contaminate the interior fluid passages in the caliper.

Installation

•Adapter fitting into caliper:

Torque to 125 **in-lb** (wrench size = 7/16")

- •Bleed screw fitting: Torque to 40 in-lb (wrench size = 1/4")
- •Use an inch-pound torque wrench only!

IMPORTANT: Read disclaimer of warranty included with the product.

- 4700 Calle Bolero • Camarillo. CA 93012 • Phone 805/388-1188 • www.wilwood.com

DS-1573 REV DATE 01-17-24



READ BEFORE USING

INSTALLATION INSTRUCTIONS FOR TWO-PIECE BLEED SCREW – METRIC THREAD STYLE ADAPTER

General Information

- •Bleed screw and adapter fitting should both be installed with clean, dry threads.
- •Do not use sealant or thread locking compound on bleed screw or adapter fitting.
- •Do not contaminate the interior fluid passages in the caliper.

Installation

•Adapter fitting into caliper:

Torque to 125 in-lb (wrench size = 7/16")

•Bleed screw fitting:

Torque to 40 **in-lb** (wrench size = $\frac{1}{4}$ ")

•Use an inch-pound torque wrench only!

IMPORTANT: Read disclaimer of warranty included with the product.

4700 Calle Bolero • Camarillo, CA 93012 • Phone 805/388-1188 • www.wilwood.com