



# WILWOOD MPS ROTORS FOR HARLEY-DAVIDSON MOTORCYCLES

Wilwood mirror polished stainless (**MPS**) rotors combine the ultimate in performance and distinctive style for production bikes and full customs using OE dimension brake components. A proprietary finishing process on a select stainless alloy provides a second-to-none deep mirror finish (also available in a satin finish), and the stopping power you expect from the world leader in high performance brake systems.

- Front and rear rotors are available for most models from 1984 through 2006 that use 11.50" diameter discs with the 5" X 3.25" mounting pattern
- Symmetrical front rotors can be used on single or twin front caliper models
- Engineered drill patterns balance thermal stability with high tech style
- Close tolerance detail machining provides a precision fit without run-out or knock-back for smooth engagement at all speeds
- Specially selected stainless alloy provides full corrosion resistance and high friction with OE, metallic, and other performance compound pads
- MPS rotors can be used as a direct replacement with the OE calipers or coupled with Wilwood GP calipers and high performance BP-10 compound pads as the ultimate combination of all out stopping power and distinctive show winning style



**11.50 Front Rotor**



**11.50 Rear Rotor**

### ORDERING INFORMATION: WILWOOD HARLEY-DAVIDSON ROTORS, SPECIFICATIONS, PART NUMBERS:

DIAMETER	WIDTH	BOLT CIRCLE	HOLE TYPE	LBS	MODEL YEAR	FRONT/REAR	PART NUMBER
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.344"	4.5	1984-1999	FRONT	160-9913P
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.422"	4.5	1984-1999	REAR	160-9914P
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.344"	4.5	2000-UP	FRONT	160-9915P
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.422"	4.5	2000-UP	REAR	160-9916P
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.344"	4.5	1984-1999	FRONT	160-10662
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.422"	4.5	1984-1999	REAR	160-10663
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.344"	4.5	2000-UP	FRONT	160-10664
11.50" (292,1)	.196" (5,0)	5 x 3.25" (82,6)	.422"	4.5	2000-UP	REAR	160-10665