

STUD
CLEARANCE
.09
(2,3)

3.61
(91,7)

R .75

DISC BRAKES
wilwood

PART NUMBER

140-18298

INSTRUCTIONS

1. Print this template and verify a 1:1 scale using a ruler against both axes provided before proceeding. Adjust print scale percentage if necessary.
2. Adhere template smoothly to a piece of cardboard or sturdy construction paper.
3. Measure wheel center hole diameter. Find corresponding measurement shown in **Wheel Center Hole Diameter Chart**. Cut template following the bold, dashed lines and along the matching center hole diameter lines.
4. Fit template into wheel and determine if adequate clearance is present. A minimum of .080" clearance must be maintained between the wheel and caliper in all areas.
5. Minimum wheel center hole diameter is **2.50"**.

FITMENT NOTES

- Actual parts may vary. Use this template as a guideline to determine your wheel clearance before attempting installation.
- The wheel clearance diagram is intended for general fitment purposes. **DO NOT** rely on this diagram to make custom wheels. Have the wheel company contact Wilwood for a 3D model of the brake kit before making custom wheels.

SCALE

INCH

1

2

3

REV DATE: 11-11-25


5

4

3

2

1



Wheel
Mount
Surface

.18
(4,6)

7.36
(186,9)

4.39
(111,5)

2.87
(72,9)

2.75
(69,8)

2.62
(66,5)

2.50
(63,5)

Wheel Hub
Center Line

Wheel
Center Hole
Diameter
Chart