

BP-28 HIGH-PERFORMANCE BRAKE PADS

Wilwood's **BP-28** high-performance compound is becoming a favorite for many different applications. The unique properties lend itself to many environments and set ups. It preforms well at high temperatures with medium-to-high friction use when running stainless steel or titanium rotors. Likewise, it shines at low-to-medium temperatures in medium friction applications on steel or iron rotors.

- WIDE APPLICATION USE
- HIGH TEMP, MED-HIGH FRICTION



APPLICATIONS:

- Off-Road racing
- North East Dirt Modified
- Road Race - Lighter vehicles
- Drag racing - stainless steel
- Sprint/Midget
- Track Day cars
- Dirt Late Model
- Open Wheel Modified / Stock Car

KEY FEATURES:

- Unique feature for multiple applications
- High-temperature with medium-high friction for titanium/stainless rotors
- Low-med temperature with medium-friction on steel/iron rotors
- Predictable, consistent pedal feel
- Med-high pad wear on titanium
- Medium-low pad wear on steel/iron

ORDERING INFO: PH: 805.388.1188 • wilwood.com • info@wilwood.com

CALIPER FITMENT	PAD TYPE	THICKNESS	PART NO. - Axle Set
GP200	4908-28	.31"	150-28-4908K
GP320	6211-28	.44"	150-28-6211K
Aero 4 /6 /DM	6617-28	.67"	150-28-6617K
Aero 4 /6 /DM	6620-28	.80"	150-28-6620K
DynaPro6	6712-28	.49"	150-28-6712K
DynaPro Single	6812-28	.50"	150-28-6812K
Dynalite	7112-28	.49"	150-28-7112K
Superlite 4/6, Narrow	7416-28	.65"	150-28-7416K
Superlite 4/6, Wide	7420-28	.80"	150-28-7420K
AT6	7516-28	.625"	150-28-7516K
Grand National	7520-28	.80"	150-28-7520K
Dynapro / UTV4/6	7812-28	.49"	150-28-7812K
Narrow Dynalite / DynaPro	7816-28	.60"	150-28-7816K
Powerlite	7912-28	.49"	150-28-7912K
D154, GM Metric	D154-28	.52"	150-28-D154K
D52, GM (Inners, Outers)	D0052-28	.58" & .52"	150-28-D52K
XRZ	10420-28	.80"	150-28-10420K

